

Object preserved from unsetting after template parsing # These are meant for referencing

```
lib.stdheader = COA
lib.stdheader {
    stdWrap.wrapAlign = eld = header_position
    stdWrap.typolink.parameter = eld = header
    stdWrap.eldRequired = header
    stdWrap.editIcons = tt_content : header, [header_layout | header_position], [header_link|date]
    stdWrap.editIcons.beforeLastTag=1
    stdWrap.editIcons.iconTitle=Edit header
}
```



Certificate

Heiko Hardt

has fulfilled all the requirements and has
officially become a

Certified TYPO3 CMS Integrator

for the — version of the TYPO3 content
management system.

This person has been specially trained and is qualified
to properly implement successful TYPO3-based solutions.
In accordance with the TYPO3 Association's guidelines
this certification gives the Certified TYPO3 CMS Integrator
the right to use this title for promotional, contractual,
and other purposes.

This certificate is valid for a period of 36
months starting with the date of issue.

27.2.2014

place and date of issue

27.2.2017

valid until



Kasper Skårhøj

Dominic Brander

```
5 = TEXT
5.eld = date
5.if.isTrue.eld = date
5.date = d/m Y
5.wrap = {$content.wrap.headerDate}
```

```
10 = CASE
10.setCurrent {
    eld = header
    parseFunc < styles.content.parseFunc
    parseFunc.if.value = 5
    parseFunc.if.equals {
        eld = header_layout
        ifEmpty = {$content.defaultHeader}
        ifEmpty.override.data = register: defaultHeaderType
    }
    parseFunc.if.negate = 1
}
```

```
10.key.eld = header_layout
10.key.ifEmpty = {$content.defaultHeader}
10.key.ifEmpty.override.data = register: defaultHeaderType
10.stdWrap.wrap = {$content.wrap.header}
```

```
10.1 = TEXT
10.1.current = 1
10.1.fontTag = {$content.wrap.header1}
10.1.case = {$content.case.header1}
10.1.wrap2 = {$content.wrap2.header1}
```

```
10.2 = TEXT
10.2.current = 1
10.2.fontTag = {$content.wrap.header2}
10.2.case = {$content.case.header2}
10.2.wrap2 = {$content.wrap2.header2}
```

```
10.3 = TEXT
10.3.current = 1
10.3.fontTag = {$content.wrap.header3}
10.3.wrap2 = {$content.wrap2.header3}
```

```
10.4 = TEXT
10.4.current = 1
10.4.fontTag = {$content.wrap.header4}
```

```
10.5 < styles.header.gfx1
stdWrap.space = {$content.headerSpace}
```

```
#
# Configuring of language for backwards compatibility # ($comment_OK) con g language = dk
```

```
#
# tt_content is started
```

```
tt_content >
tt_content = CASE
tt_content.stdWrap {
    spaceBefore.eld = spaceBefore
    spaceAfter.eld = spaceAfter
    space = {$content.space}
    innerWrap.cObject < styles.content.frame
    innerWrap2 = 1 {$content.linkToTop}
    innerWrap2.eldRequired = linkToTop
    dataWrap = <a id="c[eld:uid]"></a>
    editPanel = 1
    editPanel {
        allow = move,new,edit,hide,delete
        line=5
        label = %s
        onlyCurrentPid = 1
        previewBorder=4
        edit.displayRecord = 1
    }
}
```

```
tt_content.key.eld = CType
```

```
# CType: header
tt_content.header = COA
```